



Pin Khởi Động Xe Máy Công Trình

Lithium Construction Machinery Starting Battery

Lithium battery designed for direct replacement of automotive lead acid batteries.

LFP cells for fire safety and environmental friendliness.

Over-discharge cut-off batteries can be recovered by common chargers or jumpstarted.

Over-load or short-circuit cut-off batteries can be recovered by disconnecting load.

Service life can reach 2000 cycles or 8-10 years.

Constant performance in whole service life

Faulty batteries can be repaired to avoid disposal of the complete module



LEAD-TO-LITHIUM SOLUTION

CONSTRUCTION MACHINERY BATT.	BP125	BP140	BP160
Nominal voltage	12.8V	12.8V	12.8V
Cranking amperage	200A	320A	480A
Max continuous discharge amperage	60A	80A	120A
Max charge voltage	15.2V	15.2V	15.2V
Max charge amperage	45A	45A	60A
Dung lượng	12Ah	15Ah	22Ah
Dimension L x W x H (mm)	150 x 87 x 160	165 x 125 x 175	198x 165 x 170
Weight	3.1kg	4.3kg	5.8kg
Engines with cylinder displacement	Diesel upto 1.2L	Diesel upto 2.2L	Diesel upto 3.5L

CONSTRUCTION MACHINERY BATT.	BP180	BP208	BP212
Nominal voltage	12.8V	25.6V	25.6V
Cranking amperage	640A	320A	480A
Max continuous discharge amperage	160A	80A	120A
Max charge voltage	15.2V	30.2	30.2V
Max charge amperage	90A	45A	60A
Dung lượng	30Ah	15Ah	22Ah
Dimension L x W x H (mm)	208x 175 x 190	230 x 138 x 208	260 x 167 x 210
Weight	8.0kg	7.5kg	10kg
Engines with cylinder displacement	Diesel upto 7L	Diesel upto 7L	Diesel upto 15L



Office: No. 39 street 10, The Verosa Park, Phu Huu ward, Thu Duc town, HCM city, Viet Nam

Factory: D2 lot, Tam Thang industrial park, Cu Jut, Dac Nong, Viet Nam

+84 866 220 121 | info@vibatco.com | www.vibatco.com